



Figure similar

SOLKOR R-CIRCULATING CURRENT FEEDER PROTECTION SELF RESET
CONTACTS CONTACT ARRANGEMENT: 3 NO,0 NC SOLKOR MODE: SOLKOR
R HOUSING SIZE: CASE SIZE E6 (4U HIGH) RATING: 5A AC

Protection Functions	
three-pole tripping	Yes
teleprotection scheme (ANSI 85)	Yes
differential protection, line (ANSI 87L)	Yes
Supply voltage	
line frequency	50 ... 60 Hz
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	3
number of digital outputs / incl. signaling contact / maximum	3
number of current inputs / maximum	3
Mechanical Design	
width	155 mm
height	177 mm
depth	247 mm
frame size of enclosure	E6
Environmental conditions	
ambient temperature / during operation / maximum	55 °C
Further information	

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2111-1DA30-1DD0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/7PG2111-1DA30-1DD0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2111-1DA30-1DD0

Tender specifications
<https://www.siemens.com/specifications>

Power Academy - Your training and consulting partner in the area of power transmission and distribution
<https://www.siemens.com/poweracademy>

