



Figure similar

RELAY SOLKOR PILOT SUPERVISION SUPPLY TRANSFORMER/RECTIFIER UNIT (SEND END), NO FLAG, CONTACT ARRANGEMENT: 0NO/0NC
INSULATION LEVEL: 5KV CASE SIZE E4 (4U HIGH) RATING: 110/220/240V AC,50/60HZ

Supply voltage	
supply voltage / at AC	110 ... 240 V
type of voltage / of the supply voltage	AC
line frequency	50 ... 60 Hz
Mechanical Design	
width	103 mm
height	177 mm
depth	247 mm
frame size of enclosure	E4
Environmental conditions	
ambient temperature / during operation	55 °C
ambient temperature / during operation / maximum	55 °C
Further information	

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PG2120-0AA00-1CA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/7PG2120-0AA00-1CA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PG2120-0AA00-1CA0

Tender specifications
<https://www.siemens.com/specifications>

Power Academy - Your training and consulting partner in the area of power transmission and distribution
<https://www.siemens.com/poweracademy>

